
KW-600, 900, 1200

盐雾试验机

Salt Spray Tester



Structure Characteristics:

- 1.Entire housing is manufactured from non-corrosive PVC panel to ensure firm framework and durable long life time use.
- 2Automatic, manual watering system, water shortage has automatic / manual reinforcing water function, test without interruption.
- 3.Precise glass nozzle design ensures 4000 hours normal working performance without crystal choke.
- 4.Control instrument are all in the same machine plate, simple operation,and be clear at a glance.
- 5.A dual over-temperature protection, water level warning, ensure the safety of use.
- 6.High precision temperature controller with functions of digital display, PID control and thermometer with built in platinum detector providing reliable measurement (tolerance:±0.3℃).
- 7.Spray was heated directly in transfer trough, which is efficient and time-saving
- 8.Spray generator with built in cone-shape scatter has functions of spray direction guide, quantity control and ensures uniform fine water spray .
9. The pressure barrel using Henry's law, in order to heating and humidifying,and provide the required humidity of the laboratory.

KW-600, 900, 1200

盐雾试验机

Salt Spray Tester

Technical:

Field of application	ISO-9227 人造气氛腐蚀试验 - 盐雾试验		
	ASTM-B117 盐雾试验方法		
	JIS-D0201 自动车部品-电气通则		
	JIS-H8502 金属覆层防腐性试验方法		
	JIS-H8610 钢铁上的电镀锌层		
	JIS-Z2371 盐雾试验方法		
	GB/T 10125 人造气氛腐蚀试验 盐雾试验		
Model No	KW-600	KW-900	KW-1200
Laboratory size (mm)	600*450*400	900*600*500	1200*1000*500
Meas (mm)	1075*630*1185	1415*885*1285	1900*1200*1400
Lab volume	108L	270L	600L
Brine tank volume	15L	25L	40L
Spray way	A:Continuous salt spray test machine		
	B:Programmable salt spray test machine		
Test chamber temperature	Saline test 35°C±1°C/corrosion resistance test 50°C±1°C		
Saturated barrel temperature	Saline test 47°C±1°C/corrosion resistance test 63°C±1°C		
PH	Saline test (6.5~7.2)/corrosion resistance test (3.0~3.2)		
Spray volume	1.0~2.0ml/h		
Relative humidity of the laboratory	> 85%		
Concentration of sodium chloride solution	5%		
Power	AC220V1 ∅ 10A	AC220V1 ∅ 15A	AC220V1 ∅ 20A



Kingwells

东莞市锦辉试验设备制造厂

Kingwells Test Equipment Mfg., Ltd.

地址: 广东省东莞市南城区白马方屋坵村1巷1号

电话: 86-769-22906718 传真: 86-769-22909619

Web: www.kingwells.com.cn www.kingwells.com

E-Mail: info@kingwells.com.cn