

KW-01
锐利边缘测试器
Sharp Edge Tester

注册专利:
ZL 2011 3 0305840.6



Technical:

Test object	Safety Testing: evaluate all assecible edges that presents an unreasonable risk of injury during normal use and reasonably foreseeable abuse of a toy			
Field of application	American		Europe	China
	16 CFR 1500.49	ASTM F963 4.7	EN-71 1998 8.2	GB 6675-2003 A.5.9
Spindle diameter	0.375"(+0.005"/-0.002")	Specification per 16CFR 1500.49	9.53 (+0.12/-0.12) mm	9.53 (+0.12/-0.12) mm
Force	1.35lbf(6.0N)		6(+0.5/-0.5)N	6(0/-0.5)N
Spindle swivel rate	1"(+0.08"/-0.08")/S		23(+4/-4)mm/s	23(+4/-4)mm/s
Spindle surface roughness	≤ 0.10um		≤ 0.10um	≤ 0.10um
Hardness	≥ HRC40			
power adapter	Toshiba; input 110-220VAC, output 15VDC 5A			
Dimensions	Product:275mm×290mm×105mm			
	Package:380mm×380mm×30mm			
Weight	Product:1.85KGS			
	Package:1.8KGS			
Non Standard accessories	Saint-Gobain T-Tape			
	Sharp edges test fixed plate			



Kingwells

东莞市锦辉试验设备制造厂
Kingwells Test Equipment Mfg., Ltd.

地址: 广东省东莞市南城区白马方屋丛村1巷1号
电话: 86-769-22906718 传真: 86-769-22909619
Web: www.kingwells.com.cn www.kingwells.com
E-Mail: info@kingwells.com.cn